

# KENWOOD

# NX-700/800

## NEXEDGE®

NEXEDGE® VHF/UHF Digital & Analog Mobile Radios

*MPT-1327* \*\*  **NXDN®** FleetSync®

### ● GENERAL FEATURES

- 30 W (136-174 MHz) Models
- 30 W (400-470 MHz) Models
- 512 CH-GID / 128 Zones
- Dash & Remote Mount
- 14 Character Alphanumeric Aliases
- Backlit Dot Matrix LCD
- Function/Status LCD Icons
- Multi-Language Display
- Date & 12/24 Hour Time Clock
- Transmit/Busy/Call Alert/Warn LED
- On/Off Power Control
- 4 Up/Down Selectors
- 6 Front PF Keys
- Emergency/AUX Key
- 4W Speaker Audio
- DB-25 Accessory Connector
- 9 Programmable AUX I/Os
- 2 Programmable AUX Outputs
- KPG-111D Windows® FPU
- Flash Firmware Upgrading
- MIL-STD-810 C/D/E/F/G
- IP-54/55 Water & Dust Intrusion
- PC Serial Interface
- SDM Manual Input<sup>1</sup>
- Transparent Data Mode<sup>1</sup>
- GPS Receiver Option
- VGS-1 Voice Guide / Voice & GPS Data Storage Option

### ● DIGITAL – COMMON

- NXDN® Digital Air Interface
- AMBE+2™ VOCODER
- 6.25 & 12.5 kHz Channels
- Over-the-Air Alias
- Over-the-Air Programming
- Paging Call
- Emergency Call
- All Group Call
- Status Messaging<sup>1</sup>
- Remote Stun/Kill<sup>1</sup>
- Remote Check<sup>1</sup>
- Short & Long Data Messages<sup>1</sup>
- GPS Location with Voice<sup>1</sup>
- NXDN® Scrambler Included
- \*\*P25 Digital Upgradeable

### ● DIGITAL CONVENTIONAL MODE

- 64 Radio Access Numbers (RAN)
- Individual & Group Selective Call
- Mixed FM/Digital Operation
- Conventional IP Networks
- Site Roaming

### ● DIGITAL TRUNKING MODE

- Individual Private Call
- Group Call & Broadcast Call
- Transmission Trunked Mode<sup>2</sup>
- Message Trunked Mode<sup>2</sup>
- Call Queuing with Priority<sup>2</sup>
- Late Entry (UID & GID)<sup>2</sup>
- 4 Priority Monitor ID's<sup>2</sup>
- Remote Group Add<sup>1</sup>
- Failsoft Mode

### ● MULTI-SITE IP NETWORKS COMPATIBLE

- Individual Private Call
- Group Call & Broadcast Call
- Transmission Trunked Mode<sup>2</sup>

### ● SCAN

- Single Zone / Multi-Zone / List Scan
- Dual Priority Scan (Conventional)




## Options

**KMC-35**  
Microphone



**VGS-1**  
Voice Guide  
& Storage Unit



**KAP-2**  
Horn Alert  
/ PA Relay Unit



**KCT-46**  
Ignition Sense Cable



**KMC-36**  
Microphone  
with Keypad




**KRK-10**  
Panel Remote Kit



**KCT-23M**  
DC Cable (10 feet)



**KMB-10**  
Key Lock Adapter



**KMC-9C**  
Control Station  
Desktop Microphone



**KPS-15**  
DC Power Supply



**KCT-23M3**  
DC Cable (23 feet)

KCT-23M3

**KLF-2**  
Line Noise Filter



## Main Specifications

All accessories and options may not be available in all markets. Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

		NX-700(H) K	NX-800(H) K
<b>GENERAL</b>			
Frequency Range	Type 1	136-174 MHz	
	Type 2	400-470 MHz	
Number of Channels		512	
Zones		128	
Max. Channels per Zone		250	
Channel Spacing	Analog	12.5 / 15 / 25 / 30 kHz	12.5 / 25 kHz
	Digital	6.25 / 12.5 kHz	6.25 / 12.5 kHz
Operating Voltage		13.6 V DC ± 15%	
Operating Temperature Range		-22° F to +140° F (-30° C to +60° C)	
Frequency Stability		± 1.0 ppm	
Antenna Impedance		50 Ω	
Dimensions (W x H x D)	Projections not included	6.30 x 1.77 x 6.18 in (160 x 45 x 157 mm)	
Weight (net)		3.04 lb (1.38 kg)	
IC Certification	K Type 1	282F-378600	
	K Type 2	282F-378701	

Analog measurements made per TIA/EIA 603 and specifications shown are typical. Kenwood reserves the right to change specifications without prior notice or obligation.

FleetSync® is a registered trademark of JVCKENWOOD Corporation.

LTR® is a registered trademark of Transcript International.

AMBE+2™ is a trademark of Digital Voice Systems Inc.

Windows® is a registered trademark of Microsoft Corporation.

NXDN® is a registered trademark of JVCKENWOOD Corporation and Icom Inc.

NEXEDGE® is a registered trademark of JVCKENWOOD Corporation.

		NX-700(H) K	NX-800(H) K
<b>RECEIVER</b>			
Sensitivity	Digital @ 6.25 kHz (3% BER)	0.20 µV	
	Digital @ 12.5 kHz (3% BER)	0.28 µV	
	Analog (12 dB SINAD)	0.25 µV	
Selectivity	Analog @ 25 kHz	80 dB	
	Analog @ 12.5 kHz	70 dB	
Intermodulation	Analog	75 dB (±50,100 kHz)	
Spurious Response	Analog	90 dB	85 dB
Audio Distortion		Less than 3%	
Audio Output		4 W / 4 Ω	
<b>TRANSMITTER</b>			
RF Power Output		30 W to 1 W	30 W to 1 W
Spurious Response		73 dB	75 dB
FM Hum & Noise	Analog @ 25 kHz	50 dB	
	Analog @ 12.5 kHz	45 dB	
Audio Distortion		Less than 3%	
Modulation		16K0F3E, 14K4F1D, 11K0F3E, 8K30F1E, 8K30F1D, 8K30F7W, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D	

footnotes from Front:

<sup>1</sup> Requires NX subscriber unit PC Serial Interface compatible software application (e.g. Kenwood AVL & Dispatch Messaging software) or hardware (e.g. console).

<sup>2</sup> These trunked features are primarily system programming and operational dependent. Priority Monitor also requires NX subscriber settings.

## Applicable MIL-STD & IP

MIL Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II	500.5/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II	501.5/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II	502.5/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II	503.5/Procedure I
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I	505.5/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III	506.5/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4	507.5/Procedure II
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4	509.5
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III	510.5/Procedure I
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I	514.6/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV	516.6/Procedure I, IV
<b>International Protection Standard</b>					
Dust & Water Protection	IP54: Radio itself				
	IP54/55: Remote head with KRK-10				

# KENWOOD

Kenwood Electronics Canada Inc.  
Canadian Headquarters and Distribution  
6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8  
www.kenwood.ca



ADS#48712 Printed in CANADA