
Man-Overboard Alarm/Locator







When a crewmember falls overboard, the water-activated ALERT2 Transmitter sends a radio signal to the ALERT On-Board Receiver, sounding a 95 dB alarm and marking your position on a compatible GPS or loran. The ALERT Receiver can also be wired to shut down an engine, or disable the autopilot, offering a margin of safety for the single-handed operator.

Used by the US Navy, US Coast Guard, Pilot Vessels, Tug Boats, Fishing Vessels, Powerboats and Offshore Sailboats

The ALERT Direction Finder is a rugged hand-held directional antenna that plugs into the ALERT Receiver, allowing the user to search for the victim's ALERT Transmitter signal by manually sweeping the horizon while monitoring the antenna's 100dB alarm and light.

Specifications

AT100 Transmitter:

Weight: 4oz. with batteries Dimensions: 5.5"x1.5"x.75"

Watertight integrity: 200 feet water depth, maximum Power supply: Two 3.6 volt AA lithium batteries

Controls: Off/Armed/Manual On

Attachment: Nylon pouch

FCC Approval: Part 15 (no license required)

Frequency: 418 MHz

Range: One mile maximum

Antenna: Internal

Operating life: Three hours minimum at -4°F (-20°C)
Battery replacement: Annual or upon emergency use

Low battery indicator: Steady red LED

Operating temperature: -4°F to 130°F (-20°C to 55°C)
Storage temperature: -40°F to 158°F (-40°C to 70°C)

For maximum protection always wear personal flotation and mount the ALERT2 high on the chest.

AR100 Receiver:

Power supply: 12 volt, 100mA, external

Dimensions: 6" x 5" x 1.5" Weight: 12 oz.

Mounting: Bracket, vertical or horizontal

Antenna: 18" whip with 25 ft. coax
Internal alarm: 95 dB, front panel mounted
Remote alarm/GPS/ Relay contacts: normally open,
and normally closed, 1A max
Operating temperature: -4°F to 130°F (-20°C to 55°C)
Storage temperature: -40°F to 158°F (-40°C to 70°C)

ADF100 Direction Finder:

Dimensions: 19" x 15" x 3"

Weight: 2 lbs.

Cable: 25 ft. coax, included Indicators: 100 dB horn w/red LED Specifications subject to change without notice



(800) 426-4201